



CHARACTERISTICS / MODEL

		Super Chik-30	Super Chik-35	Super Chik-45	Super Chik-50	Super Chik-60
Production	Speed (packs./min)	30	35	45	45	60
	Fixed / Variable	Fixed	Fixed	Variable	Variable	Variable
Size of the trays (Maximum and minimum incompatible)	Length	177.8 - 355.6 mm (7"-14")				
	Width	101.6 - 228.6 mm (4"-9")				
	Height	9.5 - 177.8 mm (3/8"-7")				
	Wrap without tray	NO				
Tray size change		Manual	Automatic	Automatic	Manual	Manual
Roll of film	Maximum diameter	225 mm				
	Thickness	13-20 micras Depends on the film				
	Diameter of roll	76.2 mm (3"); With SSD film 152.4 mm (6")				
	Width	355.6 - 609.6 mm (14"-24") (Maximum and minimum incompatible)				
	N° of rolls	1	2	2	1	1
Type of Film	PVC	S	S	S	S	S
	PE (Polyethylene)	O	O	O	O	O
	SSD (Polyolefine)	O	O	O	O	O
Printed Film		O	O	O	O	O
Electric power	Voltage	230/400V. 3 Phase +- 10% + N. + T. - 50/60 Hz.				
	Consumption	2.5Kw/6 Amp. -> 400V; 10 Amp.-> 230V				
Pneumatic consumption		Until 60 NL/Min a 6 bares (Ask to model of machine and options)				
Aproximate weight		1220 Lbs.				

(S= Standard; O= Option; Not possible= NO) (*) Lengths chosen by selector.

ULMA reserves the right to change specifications without prior notice.



ULMA Packaging

Thanks to an experience of more than 50 years, we are a worldwide reference in the design and manufacturing of high-tech packaging systems and equipment.

More than 50 years evolving, innovating, perfecting our technology and our services. An extensive network that is available to offer you solutions anywhere in the world, and to fully satisfy customers that place their trust in us.

For additional information, please visit our website:

www.ulmapackaging.com

CO183

Global Packaging



ULMA Packaging, S. Coop.
B° Garibai, 28 - Apdo. 145
20.560 OÑATI (Gipuzkoa) SPAIN
Tel.: +34 - 943 73 92 00
Fax: +34 - 943 78 08 19
Web: www.ulmapackaging.com
e-mail: info@ulmapackaging.com

SUPER CHIK
Stretch Film

| EN

Tray Wrapping Machine



A high performance wrapping machine, specially developed for the wrapping of trays in central processing facilities (meat, poultry, fish, produce, ...), and high volume supermarkets. A large range of models for customer requirements.

Its strength, reliability, ease of operation, and automatic size change, make it the most productive and versatile machine available, possibility to wrap with several kinds of film: PVC, polyethylene and polyolefines.

TECHNICAL FEATURES (Depends on the model)

- 1 or 2 film rolls with automatic roll selection.
- Automatic recognition of the tray dimensions or manual.
- Automatic or manual selection of film length and width.
- Universal elevator.
- Self diagnostic capability.
- Film tension control.
- Forward and reverse jog capability.
- 4-way film stretch with lateral pre stretch.
- Temperature control for the sealing belt.
- Over size package detector.
- Mechanical torque limiter.
- Guards and safety devices according to international standards.
- Heavy duty construction with corrosion resistant material. USDA approved.

OPTIONS

- Automatic infeed conveyor with tray centering device.
- Extended infeed conveyors.
- Centralized lubrication.
- Sanitary clean out tray.
- Gravity and motorized exit conveyors: in line, 90°, 180°, ...
- Additional 1 meter sealing device.
- Automatic image centering device for printed films.
- Printed band attachment.
- Transparent tray detection.
- Sealer Cooler.
- Others (Ask).

Super Chik



Automatic image centering device for printed film



Sealer cooler



Automatic infeed conveyor with tray centering device



Lubrication



Gravity and Motorized Conveyors